

TOP GLOVE
TOP QUALITY, TOP EFFICIENCY



DIAMOND SANDBLAST NITRILE GLOVES




**EXCEPTIONAL
GRIP IN DRY,
WET AND OILY
CONDITION**

APPLICATION



Automotive Industry



Heavy Industry



Arm Force




Construction



Gardening



General Lab Use



Diamond Sandblast Nitrile Glove combines hybrid texture of sandblast and diamond. This robust and durable glove features an exclusive “Hybrid Diamond Sandblast” pattern positioned on the palm and finger surface for a better gripping experience.

The internal texture of the glove provides a good "skin-to-glove" grip that minimises slippage. The glove is engineered in a way that it moulds perfectly to your hand for comfort and maximum dexterity.

DIAMOND SANDBLAST NITRILE GLOVES

Quality Standards

- Manufactured under QSR (GMP), ISO 9001:2015 and ISO 13485:2016 Quality Management System
- Conforms to ASTM D6319 and EN455 Standards

Glove Sizes

- Medium, Large, Extra Large, Extra Extra Large

Product Specifications

- Type** : Powder Free, Non-Sterile
Material : Synthetic Nitrile Latex
Colour : Black, Orange, Apple Green, Blue
Design & Features : Diamond Sandblast Textured, Ambidextrous, Beaded Cuff, Online Single Chlorinated
Storage : The gloves shall maintain their properties when stored in a dry condition. Avoid direct sunlight
Shelf Life : 3 years from the date of manufacturing



Better Grip



Chemical Resistance



8 Mil Thickness


Physical Dimension

Description	Standards		
	Top Glove	ASTM D6319	EN 455
Length (mm)	Min 240 300 ± 10	Min 230 (M, L, XL, XXL)	Min 240
Palm Width (mm)			
• M	94 ± 3	95 ± 10	95 ± 10
• L	105 ± 3	110 ± 10	110 ± 10
• XL	113 ± 3	120 ± 10	≥ 110
• XXL	123 ± 3	130 ± 10	N/A
Thickness : Single Wall (mm)			
Finger	0.20 ± 0.02mm (8.0 ± 0.8 mil)		N/A
Palm	0.07 ± 0.02mm (4.8 ± 0.8 mil)		N/A

Physical Properties

Description	Standards	
	ASTM D6319	EN 455
Tensile Strength (MPa)		
• Before Aging	Min 14	N/A
• After Aging	Min 14	N/A
Elongation at Break (%)		
• Before Aging	Min 500	N/A
• After Aging	Min 400	N/A
Median Force at Break (N)		
• Before Aging	N/A	Min 6
• After Aging	N/A	Min 6

TEXTURE CLOSE UP



**Hybrid
Diamond +
Sandblast
Texture**



DP180124/TGT

If you have any enquiries on our products, please contact :

TOP GLOVE SALES & CORPORATE OFFICE

Top Glove Tower, 16, Persiaran Setia Dagang, Setia Alam, Seksyen U13, 40170 Shah Alam, Selangor D.E., Malaysia.

+603 3362 3098

+603 3362 5096 (Sales)

SCAN FOR MORE PRODUCT INFORMATION



SCAN TO PROVIDE FEEDBACK AND VISIT OUR WEBSITE



sales@topglove.com.my

https://www.facebook.com/topglovecorp

www.topglove.com